

# MINIFLOW RAPID

## Cable blowing machine for access network

### Rugged stainless construction

The machine is designed based on functionality including:

- Safety chain guard
- Adjustable knobs
- Push force indicator

### Fast cable blowing

The machine is capable of installing fiber cable at a speed up to 100 m/min. and up to a distance of 3.5 km making it a compact and efficient cable blowing machine.

### Built-in electronic counter and tachometer

The counter is easy to read, robust and simple to operate.

### Robust and compact

The machine is constructed in stainless steel and anodized aluminium, which makes it suited for use under rugged conditions at cable blowing locations.

### Flexible

The machine can quickly be adapted to accommodate different cable and duct sizes making it flexible to fit every fiber blowing job.


## DON'T FORGET TO ORDER

Hydraulic Power Pack/Control valve and high pressure compressor.

Item No.: 101-10102 & 101-10103

### Cable damage safety

MiniFlow RAPID has a unique monitoring system, which continuously monitors the pushing force applied on the fiber cable. This makes it easy to stop the process before any damage happens to the cable.



## SPECIFICATIONS

Item No.:	101-10031
Cable diameter <sup>1</sup> :	3-12 mm
Duct diameter:	7-20 mm
Blowing distance <sup>2</sup> :	Up to 3500 m
Blowing speed <sup>2</sup> :	Up to 100 m/min
Pushing force:	0-40 kg
Recommended pressure and airflow <sup>3</sup> :	8-16 bar (1,000 l/pr. min.)
Weight:	24 kg
Length:	650 mm
Width:	225 mm
Height:	210 mm

<sup>1</sup> Two sets of chains needed (3-8 mm/4-12 mm).

<sup>2</sup> Depending on type of microduct and cable.

<sup>3</sup> Cooled and dried air.

