

DATASHEET

RUNPOCAM RC2 30 M + PROFI SET - 50 M FOR PIPE INSPECTION FOR LONG DISTANCES UP TO 50 M



Item no.: 11140



Click here Video

Click here Product information

CAMERA WITH REEL + MONITOR + CASE + INCLUDED ACCESSORIES:



- A. RUNPOGLIDER with front thread
- B. Micro memory card 8 GB / adapter
- C. Connection thread set (blind cap, inside and outside connection thread)
- D. SYSTEMGLIDER RC2
- E. Fishing hook
- F. Magnet fishing-set
- G. High-performance 320-lumen rechargeable LED lamp (protection rating IP 67)
- H. Dual USB charging adapter 12 V
- I. Flexible attachment 12 cm
- J. USB / Micro-USB charging cable 3 m
- K. USB charging cable for LED battery Lamp
- L. Thread attachment RC2
- M. Dual USB charging adapter 230 V

DATA

ITEM NO.	11140
CABLE LENGTH m	30 m
TOTAL WEIGHT KG	2,90 kg
CASE SIZE MM	B 395 mm L 434 mm H 135 mm
MONITOR	3.5" TFT LCD Monitor 16 M color
CAMERA PROBE	307.200 Pixel (640 x 480)
ILLUMINATION	6 x LED (integrated in camera probe)
PROTECTION CLASS	IP 67 (camera probe and cable)
FIELD OF VIEW	64 °
FOCUSSING DISTANCE	30 mm – 80 mm
POWER SUPPLY	230 V or battery-operated (battery included)
LANGUAGES	DE, EN, FR, ES, PT, IT, NL, DA, SE, NO, FI, PL, CS, HU, RU, IS, LT, SK, SLO, HR, TR
EAN-CODE	9120045476392

ADVANTAGES

- Protection class IP67
- Pipe inspection from Ø 14 mm (inside)
- Ventilation pipes, drainage pipes, sewage pipes and much more
- Also for cavity inspection and suspended ceilings
- Lengths 10 m, 30 m or 50 m
- Memory function/documented evidence
- Photo (JPG), Video (AVI) and Audio
- Spool with camera cable can be easily unwound or rewound via the X BOARD series

DESCRIPTION

RUNPOCAM RC2 multifunctional camera with cable lengths of 10 m, 30 m and 50 m with coil incl. monitor bracket. In W-Boxx system case - compatible with Sortimo. Extra large 3.5" TFT LCD 16 m colour display, protection class IP67 (camera probe and cable), battery operation up to 6 hours. Evidence preservation/storage function: photo, video and audio. CAMERA HEAD with 6 integrated LEDs, enclosed in robust stainless steel head (Ø 13 mm) with RTG Ø 6 mm internal thread. Compatible to all RUNPOTEC products with RTG Ø 6 mm thread (POWER REX, RUNPOSTICKS, RUNPO 1, glass fibre rod Ø 4.5 - 6 - 7.5 - 9 - 11 - 15 mm).

Optimal field of application: For pipe inspections over long distances of up to 50 m. As of 14 mm inner diameter (corresponds to empty pipe Ø 20 mm), but also for larger pipe cross-sections (ventilation systems, drainage systems, sewage pipes etc.). In combination with the RUNPOSTICKS, excellent for cavity wall inspections, suspended ceilings (above high ceiling profiles), manhole and underfloor ducts, maintenance and system inspections.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: RUNPOCAM RC2 with cable incl. reel in system case and incl. accessories: RUNPOGLIDER with front thread, system slide, LED-battery high performance 320 lumen lamp, Micro Memory Card 8 GB, magnetic catch set, connecting thread set RTG Ø 6 mm, catch hook, 2-fold USB charging plug 12 V, flexible attachment 12 cm, USB cable 3 m, 2-fold USB charging plug 230 V, threaded attachment RC 2, USB charging cable for LED-battery lamp

INFORMATION

Combinable plug systems:

- RUNPO 1**
Length 5 - 30 m  [Click here Product information](#)
- POWER REX**
Length 20 m | 30m | 40 m | 50 m  [Click here Product information](#)
- Fibreglass rod Ø 4,5/6/7,5/9/11 mm**
Length 30 up to 300 Meter  [Click here Product information](#)
- RUNPOSTICKS**
Paket: Comfort | Standard  [Click here Product information](#)

DATA SHEET

FIBERGLASS ROAD Ø 4,5 MM PROFI-SET

with steel cage incl. new double-outlet system

Item no.: 10052 | 10055 | 10057 | 10047 | 10050



VIDEO

Fiberglass rod
Ø 4,5 mm

Click here
Video

Click here
Productinformation

Detailed image

INCL. ACCESSORIES

BEGINNING

RUNPOGLIDER with swivel Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

Achtung!
Stromleitend
Attention!
electric
conductive

DATA					
ITEM NO.	10052	10055	10057	10047	10050
LENGTH	30 m	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	4,365	4,585	4,805	5,025	5,480
DIMENSION	H 500 / B 380 / T 250				
MATERIAL	Fiberglass core with PP sheath				
PIPE Ø	for tube diameter 30 - 80 mm				
TOTAL BREAKING LOAD	220 kg				

ADVANTAGES

- incl. steel reel
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Glass fibre rod total breaking load up to 1300 kg
- Total breaking load 220 kg
Bending radius 120 mm

Rec. tube diameter, bending radius and total breaking load for the fiberglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

DESCRIPTION

Professional set fiberglass rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 1300 kg, total breaking load 220 kg.

Optimal field of application: for pipe diameters 30 mm - 80 mm.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 piece fiberglass rod Ø 4.5 mm Profi Set incl. RUNPOGLEITER at the rod tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve, 1 x connecting sleeve, 1 x shackle, 1 x special adhesive, 1 x roller, 1 x RUNPOGLEITER with front thread

INFORMATION

Compatible with:

RUNPOCAM RC2

Length: 10 m | 30 m | 50 m

Item no. 10139 | 10140 | 10141

