

DATA SHEET

FIBERGLASS ROAD Ø 4,5 MM STANDARD-SET

with steel cage incl. new double run-out system

Item no.: 10054 | 10056 | 10058 | 10048 | 10051



VIDEO

Fiberglass rod
Ø 4,5 mm

Click here
Video

Click here
Productinformation

Detailed images:

All steel cages are equipped with a lateral locking brake and the new double run-out system (quick outlet and automatic run-out brake)

Quick run with rollers

automatic run-out brake

BEGINNING

RUNPOGLIDER with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

Achtung!
Stromleitend
Attention!
electric
conductive

DATA	Recommended retail price / excluding VAT				
ITEM NO.	10054	10056	10058	10048	10051
PRICE €	180,00	206,00	230,00	255,00	306,00
LENGTH	30 m	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	4,365	4,585	4,805	5,025	5,480
DIMENSION	H 500 / B 380 / T 250				
MATERIAL	Fiberglass core with PP sheath				
PIPE Ø	fur tube diameter von 30 - 80 mm				
TOTAL BREAKING LOAD	220 kg				

ADVANTAGES

- ✓ incl. steel reel
- ✓ Double run-out system (automatic run-out brake and fast run-out)
- ✓ Additional parking brake
- ✓ Glass fibre rod total breaking load up to 1300 kg
- ✓ Total breaking load 220 kg
Bending radius 120 mm

Rec. tube diamter, bending radius and total breaking load for the fiberglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

DESCRIPTION

Standard set fiberglass rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 1300 kg, total breaking load 220 kg.

Optimal field of application: for pipe diameters 30 mm - 80 mm.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 piece fiberglass rod Ø 4.5 mm Standard Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the rod tip and end sleeve at the rod end

INFORMATION

Compatible with:

RUNPOCAM RC2

Length: 10 m | 30 m | 50 m

Item no. 10139 | 10140 | 10141



DATA SHEET

FIBERGLASS ROAD Ø 4,5 MM PROFI-SET

with steel cage incl. new double run-out system

Item no.: 10052 | 10055 | 10057 | 10047 | 10050



VIDEO
Fiberglass rod Ø 4,5 mm
[Click here Video](#)

[Click here Productinformation](#)

INCL. ACCESSORIES

Achtung!
Stromleitend
Attention!
electric
conductive

Detailed image

BEGINNING
RUNPOGLIDER with swivel and front thread Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING
Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA	Recommended retail price / excluding VAT				
ITEM NO.	10052	10055	10057	10047	10050
PRICE €	245,00	272,00	297,00	321,00	373,00
LENGTH	30 m	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	4,365	4,585	4,805	5,025	5,480
DIMENSION	H 500 / B 380 / T 250				
MATERIAL	Fiberglass core with PP sheath				
PIPE Ø	for tube diameter 30 - 80 mm				
TOTAL BREAKING LOAD	220 kg				

ADVANTAGES

- ✓ incl. steel reel
- ✓ Double run-out system (automatic run-out brake and fast run-out)
- ✓ Additional parking brake
- ✓ Glass fibre rod total breaking load up to 1300 kg
- ✓ Total breaking load 220 kg
Bending radius 120 mm

Rec. tube diamter, bending radius and total breaking load for the fiberglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

DESCRIPTION

Professional set fiberglass rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 1300 kg, total breaking load 220 kg.

Optimal field of application: for pipe diameters 30 mm - 80 mm.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 piece fiberglass rod Ø 4.5 mm Profi Set with steel reel and new double run-out system incl. RUNPOGLEITER with swivel and front thread at the rod tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve, 1 x connecting sleeve, 1 x shackle, 1 x special adhesive, 1 x roller

INFORMATION

Compatible with:

RUNPOCAM RC2

Length: 10 m | 30 m | 50 m

Item no. 10139 | 10140 | 10141

