

DATA SHEET

GF3 Glass fiber Ø 3 mm - without metercounter Cable pulling system for pipe diameter 10-50 mm



Item no. 10196 | 10197 | 10198

CONTENT: Accessory box (18-parts)

INFO:

Front End: Guiding head with swivel and RTG Ø 6 mm front thread with kink-protection

Rear end: Kink protection with RTG Ø 6 mm inner thread

VIDEO

Click here Video

130 KG

Achtung!
Stromleitend
Attention!
electric
conductive

Click here Productinformation

DATA	*Recommended retail price / excluding VAT		
ITEM NO.	10196	10197	10198
PRICE €	€ 117,50	€ 131,00	€ 156,50
LENGTH	20 m	30 m	50 m
TOTAL WEIGHT	1,26 kg	1,40 kg	1,56 kg
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	38 mm		
PIPE Ø	optimal from 10 mm - 50 mm		
DIMENSION	L: 295 mm x B: 245 mm x H: 74 mm		
EAN-CODE	9120045477146	9120045477153	9120045477160

ADVANTAGES

- ✓ Guiding head with swivel and kink protection
- ✓ Autom. glide back protection
- ✓ Easy service access
- ✓ Shear stable - also for occupied pipes
- ✓ Extremely shockproof box with anti-slip coating
- ✓ Including cable pulling loop
- ✓ Inspektion camera RC2 compatible
- ✓ Total breaking load 130 kg

Rod	R ec. pipe diameter	Bending radius w.e.joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	10 – 50 mm	38 mm	28 mm	450 kg	130 kg
0,118"	0,394" - 1,969"	1,102"	1,102"	992,08 lbs	286,60 lbs

DESCRIPTION

GF3 - Cable pulling tool without meter counter, glass fibre rod Ø 3 mm with kink protection ending joint and patented guiding head with twist adjustment. Stowed in a shock-proof plastic box. The GF3 plastic box can be opened with only a single screw for service work. The glide-back protection prevents the fibreglass rod from accidentally slipping back into the box. Furthermore, the box has an ergonomic carrying handle and an anti-slip coating. The scope of delivery includes an 18-piece accessory set. The newly developed kink protection technology makes it possible to overcome bending radii of up to R = 38 mm. Total breaking load of 130 kg refers to the glass fibre rod incl. kink protection ending joints. The cable pulling loop (Ø 14 mm outside) with built-in twist adjustment and protective cap included can be used for one or more cables up to a cable diameter of Ø 12 mm. Quick attachment of the cables to the loop. Any plugs are protected by tensile load on the cable.

Optimal field of application: for pipe dimension 10 mm - 50 mm.

Application film: You can watch a short, very informative application film by scanning the QR code or at www.runpotec.com.

Scope of supply: 1 x GF3 without metre counter in plastic box, kink protection ending joint on both sides (start / end), contents of the accessory box: 1 x guiding head with twist adjustment, 1 x kink protection ending joint RTG Ø 6 mm, 1 x pull-in aid, 1 x special adhesive 3 g, 1 x cable pull loop (Ø 14 mm outside), 6 x adhesive sleeves Ø 3 mm, 3 x pull eyes Ø 7 mm, 1 x starting bulb Ø 11 mm, 1 x connecting sleeve, 2 x mounting-wrenches

INFORMATION

Compatible with

Inspektion camera RC2

Length: 10 m | 30 m | 50 m
Item no. 10139 | 10140 | 10141



Click here Productinformation