

DATA SHEET

REPLACEMENT GLASS FIBRE ROD

for steel cage Ø 4,5 mm

Item no.: 20311 | 20312 | 20313 | 20314 | 20315



VIDEO
Fibreglass rod 4,5 mm
[Click here Video](#)

[Click here Productinformation](#)

Repair instruction

Ø mm	A	B
4,5 mm	15 mm	10 mm

DATA	Recommended trade price in EURO / excluding VAT				
ITEM NO.	20311	20312	20313	20314	20315
PRICE €	77,70	92,40	107,00	123,80	153,00
LENGTH	30 m	40 m	50 m	60 m	80 m
WEIGHT KG	0,47	0,69	0,91	1,35	1,805
DIMENSION MM	L 400 / B 400 / H 60				
MATERIAL	Fiberglass core with PP sheath				
PIPE Ø	optimal for 30 - 80 mm				
TOTAL BREAKING LOAD	220 kg				
BENDING RADIUS	120 mm				

ADVANTAGES

- ✓ Glass fibre rod total breaking load 1300 kg
- ✓ Total breaking load 220 kg
- ✓ Bending radius 120 mm

Recommended tube diameter, bending radius and total breaking load fibreglass rod Ø 4,5 mm

Ø				
4,5 mm	30 - 80 mm	120 mm	1300 kg	220 kg

DESCRIPTION

Replacement glass fibre rod Ø 4.5 mm - RUNPOTEC RTG Ø 6 mm thread.
Glass fibre rod - total breaking load 1300 kg, total breaking load 220 kg.

Optimal field of application: for pipe diameters 30 mm - 80 mm.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 piece glass fibre rod Ø 4.5 mm with end sleeves (start/end)

INFORMATION

Suitable fibreglass rods Ø 4,5 mm (Lengths 30 - 80 Meter)

Profi Set Ø 4,5 mm

10052/10055/10057/10047/10050

Standard Set Ø 4,5 mm:

10054/10056/10058/10048/10051



[Click here Productinformation](#)



[Click here Productinformation](#)