

DATA SHEET

STARTING HEAD Ø 20 MM

for RUNPOTEC products with thread RTG Ø 12 mm

Item no.: 20409



VIDEO

Fibreglass rod Ø 7,5mm, 9 mm/11 mm

Click here Video

Click here Productinformation

Application images:

Can be adapted on roller, shackle, starting head Ø 20 mm, Ø 30 mm

Cross section:
RTG Ø 12 mm RTG Ø 6 mm

DATA	Recommended trade price in EURO / excluding VAT
ITEM NO:	20409
PRICE €	€ 22,00
TOTAL WEIGHT KG	0,055 kg
THREAD	RTG Ø 12 mm
DIMENSION	LENGTH 35 mm - Ø 20 mm
MATERIAL	STAINLESS STEEL
EAN-CODE	9120045474411

DESCRIPTION

Starting bulb Ø 20 mm made of stainless steel for glass fibre rod Ø 7.5 mm, 9 mm, 11 mm, 15 mm - RTG Ø 12 mm thread.

The starting bulb has an additional transition thread to RTG Ø 6 mm to adapt various guide rods (RUNPOSTICKS), guide probes, cable pulling sleeves etc.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 x starting bulb incl. connection thread

ADVANTAGES

- ✓ RUNPOTEC RTG Ø 12 mm
- ✓ for guide probe or smaller cable pulling sleeves
- ✓ incl. connecting thread
- ✓ Stainless steel
- ✓ leanest head

INFORMATION

RECOMMENDED PRODUCTS.

FIBREGLASS ROD Ø 7,5 mm

10076/10077/10078/10079/
10080/10091

FIBREGLASS ROD Ø 9 mm:

10081/10082/10083/10084/
10085/10086/10110

FIBREGLASS ROD Ø 11 mm:

10092/10093/10094/10095/10096/
10097

