

RP5 RUNPOTEC Polyester Ø 5,5 mm – without meter counter

optimal for pipe diameter 16–40 mm

Item no.: 10013 | 10014



Beginning:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Glide back protection
Aktive

Triple twisted special polyester fish tape Ø 5,5 mm

Ending:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Attention!
electric conductive

Very narrow bending radius

R = 15 mm

Virtually break-free even with tightest radii

R

50 % less friction resistance

Only punctual contact

Total breaking load 270 kg

Strand + Pressing + Guiding head + Eyelet

Rod	Rec. pipe-Ø	Bending radius	Total breaking load incl. RG7 - RUNPOGLIDER
Ø			
5,5 mm	16 – 40 mm	15 mm	270 kg

DATA

ITEM NO.	10013	10014
LENGTH	20 m	30 m
WEIGHT	1,31 kg	1,62 kg
EAN-CODE	9120045472806	9120045472813
DIMENSION BOX	L 380 X W 310 X H 50 mm	
TOTAL BREAKING LOAD	270 kg (on the whole strap)	
ROD Ø	Ø 5,5 mm	
MATERIAL	triple twisted special polyester fish tape	
BENDING RADIUS	15 m	
PIPE Ø	optimally from 16 mm - 40 mm	

DESCRIPTION

The RP5 - RUNPOTEC Polyester Ø 5.5 mm is a cable pulling tool without meter counter. The triple-twisted special plastic tape with a diameter of 5.5 mm has an even better shearing effect than the 3 mm fiberglass rod; the frictional resistance is only half the normal value due to spot contact. The patented RG7 guiding head with swivel Ø 5.5 mm (pressed at the beginning and end of the tape) allows overcoming tight radii (bending radius 15 mm). The RP5 Ø 5.5 mm is stored in a jobsite suitable box incl. glide back protection. The total breaking load of 270 kg refers to the entire pulling system. The cable pulling system is virtually breakage-free. The RP5 replacement strap cannot be stored in the box. **Optimal field of application:** for pipes with a diameter of Ø 16 mm - 40 mm. **Application video:** a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com. **Scope of supply:** 1 x RP5 RUNPOTEC Polyester Ø 5,5 mm without meter counter in a plastic box, including 2 x RG7 RUNPOGLIDER with swivel (pressed on both sides)

ADVANTAGES

- Total breaking load 270 kg
- 2 x RG7 - Guiding head with swivel Ø 7 mm
- Glide back protection
- Triple twisted special plastic tape Ø 5,5 mm
- 50 % less frictional resistance
- Virtually break-free, even with the tightest radii

INFORMATION

Compatible accessories:
RP5 Replacement fish tape
 20 m – Item no.: 20240
 30 m – Item no.: 20241



Cable pulling loop with hook
 (Quick release fastener) – set of 4
 Item no.: 10159

