


DATA SHEET

RUNPOTEC ROTATING CONNECTOR


for RUNPOTEC products with RTG Ø 6 mm

Item no.: 20251






Application image:



Seal of approval:



DATA	Recommended trade price in EURO / excluding VAT
ITEM NO.	20251
WEIGHT KG	0,015 kg
DIMENSION MM	L 32 mm x DM 11 mm
THREAD	RUNPOTEC RTG Ø 6 mm
EAN-CODE	9120045473391

ADVANTAGES

- ✓ Spare part RUNPOTEC products with RTG Ø 6 mm thread
- ✓ For connecting or extending fibreglass rods
- ✓ Stainless steel

DESCRIPTION

Rotating connector made of stainless steel. Used to connect or extend two glass fibre rods Ø 4.5 mm or 6 mm. RUNPOTEC RTG Ø 6 mm thread. However, RUNPOTEC glass fibre rods Ø 7.5 mm, 9 mm, 11 mm or 15 mm with the small dimensions Ø 4.5 mm or 6 mm can also be connected or extended. The swivel connector is also very practical in combination with the function glider or the RUNPOTEC RC 2 multifunction camera.

Scope of delivery: 1 piece connection piece rotatable with RUNPOTEC RTG Ø 6 mm thread

INFORMATION

Use with:

Fibreglass rod Ø 4,5 / 6 mm

Length 30 - 80 Meter

[Click here Productinformation](#)



RUNPOCAM RC2

Length: 10 m | 30 m | 50 m

Item no.: 10139 | 10140 | 10141

[Click here Productinformation](#)

