

CABLE GUIDE ROLLER - with DM 89 insertion tube

for shaft entry or exit versions – suitable for cables up to Ø 80 mm

Item no.: **10223**


VIDEO

CABLE GUIDE
ROLLER

Click here Video

Click here
Productinformation

Detailed drawing can be found on page 2.



Application images

**DATA**

Recommended trade price in EURO / excluding VAT

ITEM NO.:	10223
PRICE €	€ 129,00
DIMENSION	L 367 mm x W 155 mm x H 216 mm
LOAD CAPACITY	4.500 kg
NET WEIGHT	4,20 kg
MATERIAL	Caster: Aluminum / Frame: Steel
ROLLER DIAMETER	Ø 130 mm
APPLICATION AREA: TUBE	Ø 90 mm - Ø 105 mm (Inner diameter)
MAX. CABLE DIAMETER	Ø 80 mm
EAN-CODE	9120045478419

DESCRIPTION

The cable guide roller with 89 mm diameter insertion tube is designed for gently guiding cables around corners and edges with minimal resistance. It is inserted directly into the tube (inner diameter min. Ø 90 mm - max. Ø 105 mm) and ensures that cables can be pulled in safely and without friction. The integrated mounting holes allow for quick and reliable fixing of the roller with a single screw. The lightweight yet extremely robust construction significantly reduces the effort required and enables efficient work. High-quality, heavy-duty die-cast aluminum rollers with integrated stainless steel ball bearings and the sturdy, powder-coated steel frame ensure a long service life. The ergonomic aluminum carrying handle further facilitates handling. With a load capacity of 4500 kg, the cable guide roller is ideally suited even for demanding applications.

Optimal application: Gently and effortlessly pulling cables around corners or edges.

Scope of supply: 1 x Cable guide roller with insertion tube DM 89

ADVANTAGES

- Aluminum heavy-duty casters with stainless steel ball bearings
- Sturdy metal frame
- CDP / powder coated
- Ergonomic aluminum carrying handle
- Load capacity 4.500 kg
- Max. cable diameter Ø 80 mm

INFORMATION

Available as spare part:

POLYESTER PULL ROPE incl. reel

Rope: Ø 10 mm
 Item no.: 10167 - 120 m
 Item no.: 10168 - 200 m
 Rope: Ø 12 mm
 Item no.: 10120 - 150 m
 Item no.: 10121 - 200 m
 Item no.: 10122 - 300 m
 Item no.: 10123 - 350 m

Click here
Produktinformation

Associated pulling system:

CW 800 E Capstan winch + trolley

Item no.: 10138

Click here
Produktinformation

CABLE GUIDE ROLLER - with DM 89 insertion tube

for shaft entry or exit versions – suitable for cables up to Ø 80 mm

Item no.: **10223**