

GF15 Fiberglass rod Ø 15 mm

for pipe diameter 180 - 450 mm, incl. meter counter

Item. no. **10099** | **10100** | **10101** | **10102** | **10103** | **10104**

KG 690

Robust steel reel galvanized Basket CDP/ powder-coated

Lateral parking brake

Meter counter with hardened thumb wheel

Run-out with mounted rollers

Robust steel reel - galvanized Reel basket - CDP/powder-coated

2 x threaded bolts (for roller or starting head)

Click here Productinformation

Rod tip: Shackle, stainless steel, RTG Ø 12 mm thread, screwed to strang

Rod end: Ending joint, stainless steel, RTG Ø 12 mm thread

Run-out-system with rollers and lateral parking brake

Run-out with mounted rollers

Lateral parking brake rollers

Meter counter with hardened thumb wheel

6-digit roller counter with meter and 10 cm steps

Additional option: Adaptable leading heads

13-parts flexible leading head-set

Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
15 mm	180 - 450 mm	1200 mm	800 mm	14500 kg	690 kg

DATA

Recommended trade price in EURO / excluding VAT

ITEM. NO.	10099	10100	10101	10102	10103	10104
PRICE €	2547,00	2808,00	3093,00	3354,00	3639,00	3933,00
LENGTH	150m	200 m	250 m	300 m	350 m	400 m
WEIGHT KG	87,50	101,30	115,30	129,10	143,10	157,30
MATERIAL ROD	Fiberglass core with PP sheath					
BENDING RADIUS	1200 mm					
PIPE Ø	optimal from 180 - 450 mm					
DIMENSION	L 1558 mm B 628 mm H 1593 mm					
TOTAL BREAKING LOAD	690 kg					

DESCRIPTION

GF15 Glass fibre rod Ø 15 mm – Cable pulling tool with robust, mobile steel reel (KTL-coated/powder-coated) Ø 1400 mm, integrated metre counter, feed-out system with ball-bearing rollers and RUNPOTEC threaded RTG Ø 12 mm. The integrated metre counter, featuring a mechanical counter mechanism, a hardened knurled wheel and a 6-digit roller counter, enables precise length measurement with metre and 10-cm displays. The additional locking brake secures the reel and prevents accidental rotation. The shackle features an adapter thread to RTG Ø 6 mm, allowing various accessories such as RUNPOSTICKS, guide probes, cable pulling socks and the RC2 or RC3 inspection camera to be easily fitted. The fibreglass rod has a breaking load of up to 14,500 kg. The total breaking load, including the end sleeve, is 690 kg. The bending radius is 800 mm for the rod and 1,200 mm with the sleeve. Ideal application: for pipe diameters from 180 mm to 450 mm.

Scope of supply: 1 x GF15 Fiberglass rod Ø 15 mm, stainless steel ending joint (start/end) 1 x steel reel Ø 1400 mm mobile incl. Run-out-system with rollers, 1 x meter counter, 1 x shackle

ADVANTAGES

- Incl. steel reel and meter counter
- Run-out-system with rollers
- Additional parking brake
- Fiberglass rod breaking load 14500 kg
- Total breaking load 690 kg
- Bending radius only rod 800 mm
- Bending radius with ending joint 1200 mm

INFORMATION

Compatible with:

RC2 Inspection camera
50 m - Item no.: 10141



Click here Productinformation

RC3 Inspection camera (digital)
15 m - Item no. 10214



Click here Productinformation