

GF3 Glass Fiber Ø 3 mm - incl. digital meter counter

Cable pulling system for pipe inner diameter 9 – 45 mm

Item no.: **10192** | **10193** | **10195**

VIDEO
GF3
Click here Video

KG 130

PATENTED

Click here Productinformation

KNICKSCHUTZ KINK PROTECTION

Automatic glide back protection (only stops the RG7 Guiding head incl. kink protection)

Integrated digital meter counter – m/ft

Front end: Guiding head with RTG Ø 6 mm front thread, swivel and kink protection

Rear end: Kink protection with RTG Ø 6 mm inner thread

Attention! electric conductive

Accessory box (16-parts)

Easy service opening / accessory box

Anti-slip coating

Just open one screw

Accessory box 16-parts

Rod	Rec. pipe ID	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	9 – 45 mm	38 mm	28 mm	450 kg	130 kg

DATA			
Recommended trade price in EURO / excluding VAT			
ITEM NO.	10192	10193	10195
PRICE €	€ 184,00	€ 169,00 Offer	€ 219,00
LENGTH	20 m	30 m	50 m
TOTAL WEIGHT	1,28 kg	1,38 kg	1,58 kg
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	38 mm		
PIPE INNER Ø	optimal from 9 mm - 45 mm		
DIMENSION	L: 295 mm x W: 245 mm x H: 74 mm		
EAN-CODE	9120045476729	9120045477122	9120045477139

DESCRIPTION

GF3 - Cable pulling tool incl. digital meter counter, glass fibre rod Ø 3 mm with kink protection ending joint and patented guiding head with swivel. Stowed in a shock-proof plastic box. The GF3 plastic box can be opened with only a single screw for service work. The glide-back protection (only stops the RG7 guiding head, including kink protection) prevents the fibreglass rod from accidentally slipping back into the box. The scope of delivery includes an 16-piece accessory set. The newly developed kink protection technology makes it possible to overcome bending radii of up to R = 38 mm. Total breaking load of 130 kg refers to the glass fibre rod incl. kink protection joints.

Optimal field of application: for pipe inner dimension 9 mm - 45 mm.

Scope of supply: 1 x GF3 incl. metre counter in plastic box, kink protection ending joint on both sides (front end/rear end), contents of the accessory box: 1 x RG7 guiding head with swivel, 1 x kink protection ending joint RTG Ø 6 mm, 1 x pulling grip, 1 x special glue 3 g, 1 x cable pull loop (Ø 14 mm outside), 6 x adhesive join-set Ø 3 mm, 3 x pulling eyelet-set Ø 7 mm, 1 x starting head Ø 11 mm, 1 x connecting joint, 2 x mounting-wrench, 1 x button battery CR2032

ADVANTAGES

- Integrated digital meter counter
- Guiding head with swivel and kink protection
- Autom. glide back protection (only stops the RG7 guiding head, including kink protection)
- Easy service access
- Extremely shockproof box
- Also for occupied pipes
- Inspection camera RC2/RC3 compatible
- Total breaking load 130 kg

INFORMATION

Compatible with:

RC2 Inspection camera

30 m - Item no.: 10140

50 m - Item no.: 10141

RC3 Inspection camera (digital)

15 m - Item no. 10214

