

**GF3** Glass fiber Ø 3 mm - without metercounter

Cable pulling system for pipe diameter 10-50 mm

Item no.: **10196** | **10197** | **10198**

**VIDEO**

GF3

[Click here Video](#)

**KG 130**

**PATENTED**

[Click here Productinformation](#)

**Content accessory box (16-parts)**

**Easy service opening / accessory box**

Just open one screw      Accessory box 16-parts

| Rod  | Rec. pipe ID | Bending radius w.e. joint | Bending radius rod | Breaking load | Total breaking load |
|------|--------------|---------------------------|--------------------|---------------|---------------------|
| Ø    |              |                           |                    |               |                     |
| 3 mm | 9 – 45 mm    | 38 mm                     | 28 mm              | 450 kg        | 130 kg              |

**DATA**

Recommended trade price in EURO / excluding VAT

| ITEM NO.         | 10196                            | 10197    | 10198    |
|------------------|----------------------------------|----------|----------|
| PRICE €          | € 117,50                         | € 131,00 | € 156,50 |
| LENGTH           | 20 m                             | 30 m     | 50 m     |
| TOTAL WEIGHT     | 1,26 kg                          | 1,40 kg  | 1,56 kg  |
| MATERIAL ROD     | Fiberglass core with PP sheath   |          |          |
| BENDING RADIUS   | 38 mm                            |          |          |
| PIPE INNER Ø     | optimal from 9 mm - 45 mm        |          |          |
| DIMENSION        | L: 295 mm x B: 245 mm x H: 74 mm |          |          |
| EAN-CODE - 10192 | 9120045476729                    |          |          |
| EAN-CODE - 10193 | 9120045477122                    |          |          |
| EAN-CODE - 10195 | 9120045477139                    |          |          |

**BESCHREIBUNG**

GF3 - Cable pulling tool without meter counter, glass fibre rod Ø 3 mm with kink protection ending joint and patented guiding head with swivel. Stowed in a shock-proof plastic box. The GF3 plastic box can be opened with only a single screw for service work. The glide-back protection (only stops the RG7 guiding head, including kink protection) prevents the fibreglass rod from accidentally slipping back into the box. The scope of delivery includes an 16-piece accessory set. The newly developed kink protection technology makes it possible to overcome bending radii of up to R = 38 mm. Total breaking load of 130 kg refers to the glass fibre rod incl. kink protection ending joints.

**Optimal field of application:** for pipe inner dimension 9 mm - 45 mm.

**Application film:** You can watch a short, very informative application film by scanning the QR code or at [www.runpotech.com](http://www.runpotech.com).

**Scope of supply:** 1 x GF3 without metre counter in plastic box, kink protection ending joint on both sides (start / end), contents of the accessory box:

1 x RG7 guiding head with swivel, 1 x kink protection ending joint RTG Ø 6 mm, 1 x pulling grip, 1 x special adhesive 3 g, 1 x cable pull loop (Ø 14 mm outside), 6 x adhesive joint Ø 3 mm, 3 x pulling eye Ø 7 mm, 1 x starting head Ø 11 mm, 1 x connecting joint, 2 x mounting-wrenches

**ADVANTAGES**

- Guiding head with swivel and kink protection
- Autom. glide back protection (only stops the RG7 guiding head, including kink protection)
- Easy service access
- Shear stable - also for occupied pipes
- Extremely shockproof box with anti-slip coating
- Including cable pulling loop
- Inspektion camera RC2 compatible
- Total breaking load 130 kg

**INFORMATION**

Compatible with:

**RC2 Inspection camera**

30 m - Item no.: 10140

50 m - Item no.: 10141


[Click here Productinformation](#)
**RC3 Inspection camera (digital)**

15 m - Item no. 10214


[Click here Productinformation](#)