

GF3 Repairing Kit - 15-parts

for fiberglass rod Ø 3 mm

Item no.: **20819**

VIDEO

GF3
Click here Video

Click here ProductInformation

Stowable in accessory box

*Sample image - Box not included

Repair instructions

DATA	Recommended trade price in EURO / excluding VAT
ITEM NO.	20819
PRICE €	€ 36,80
WEIGHT	0,063 kg
DIMENSION	L 150 x B 150 x H 12 mm
CONTENT	15-parts
MATERIAL	Stainless steel and brass
VOC CONTENT	2 % (special glue)
EAN-CODE	9120045477276

DESCRIPTION

15-Part set for repairing glass fibre rods GF3 Ø 3 mm. The patented guiding head (external thread RTG Ø 6 mm) with twist adjustment is optimally suited for the GF3 glass fibre rod Ø 3 mm. The newly developed kink protection makes it possible to overcome bending radii of up to $R = 38$ mm. An extra large eyelet hole of the enclosed pulling eye ensures a higher cable capacity of up to 7×2.5 mm². One drop of the special adhesive is enough for approx. 3 - 5 cm² adhesive surface. Dries within 10 minutes - see safety data sheet for instructions! The mounting wrench can be used to tighten or loosen the guiding head with kink protection.

Application video: you can watch a short, very informative application video by scanning the QR code or on www.runpotec.com.

Scope of supply: 1 x RG7 guiding head with swivel, 2 x kink protection, 1 x special glue 3 g, 2 x mounting wrench, 1 x pulling eyelet Ø 7 mm, 6 x adhesive joints (brass), 1 x coupling joint, 1 x starting head Ø 11 mm

ADVANTAGES

- 15-parts
- Very high yield
- For repairing GF3 glass fibre rods
- Fast solution
- Dries within 10 minutes
- Stainless steel / brass sleeves

INFORMATION

Use with:

GF3 Cable pulling system

20 m - Item no.: 10192

30 m - Item no.: 10193

50 m - Item no.: 10195



Click here ProductInformation

GF3 Replacement fiberglass rod Ø 3 mm

20 m - Item no.: 20816

30 m - Item no.: 20817

50 m - Item no.: 20818



Click here ProductInformation