

GF3 SLIM Fiberglass rod Ø 3 mm – without meter counter

Cable pulling system for pipe innerdiameter 5 – 40 mm

Item no.: 10210 | 10211 | 10212



VIDEO

GF3 SLIM

[Click here Video](#)

KG 100

PATENTED

[Click here Productinformation](#)

FTTH
FIBER TO THE HOME

SLIM
Ø 4.5 mm

Automatic
Glide back protection
(only stops the RG4.5
guiding head)

RG4.5 - Guiding head with
Frontthread RTG Ø 3 mm
incl. swivel

Ending: Endind joint with
RTG Ø 3 mm, stainless steel

Attention!
Electrical
conductive

FTTH - Glass fiber installation

Speedpipe from Ø 5 mm
inner diameter

Optimally suited for occupied pipes

RG4.5 Guiding head Ø 4,5 mm

Easy service opening/ Accessory box

Anti-slip-coating

Just open one screw

Accessory box 14-parts

Content Accessorybox (14-parts)

Rod	Rec. pipe ID Ø	Bending radius	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	5 – 40 mm	40 mm	28 mm	450 kg	100 kg

DATA

Recommended trade price in EURO / excluding VAT

ITEM NO.	10210	10211	10212
PRICE €	€ 115,50	€ 129,00	€ 154,50
LENGTH	20 m	30 m	50 m
WEIGHT	1,20 kg	1,30 kg	1,50 kg
DIMENSION	L 285 mm x W 242 mm x H 65 mm		
MATERIAL ROD	Fiberglass core with PP sheath		
BENDING RADIUS	40 mm		
PIPE INNER Ø	optimal from 5 mm - 40 mm		
EAN-CODE	9120045477542	9120045477559	9120045477566

DESCRIPTION

The GF3 SLIM - Fiberglass rod Ø 3 mm is a cable pulling tool without meter counter. With a maximum diameter of just Ø 4.5 mm, it is ideal for retrofitting occupied pipes or laying fiber optic cables (FTTH - Fiber To The Home). The fiberglass rod Ø 3 mm is stored in an extremely shock-resistant plastic box. With the newly developed RG4.5 guiding head with front thread RTG Ø 3 mm including swivel, it is possible to overcome bending radii up to R = 40 mm. The automatic glide back protection (only stops the RG4.5 guiding head) prevents the fiberglass rod from accidentally slipping back into the box. The box can be opened for service work with just one screw on the back. The accessory box contains a 14-piece accessory set. The total breaking load of 100 kg refers to the glass fiber rod Ø 3 mm including RG4.5 guiding head with swivel.

Optimal field of application: for pipes with inner diameter of Ø 5 mm - 40 mm

Application film: you can watch a short, very informative application film by scanning the QR code or on www.runpotec.com

Scope of supply: 1 x GF3 SLIM without meter counter in plastic box,

1 x RG4.5 - Guiding head with swivel, contents of the accessory box: 1 x pulling grip, 1 x special adhesive 3 g, 5 x ending joint with thread RTG Ø 3 mm, 2 x mounting wrench, 2 x pulling eyelet Ø 4.5 mm, 1 x starting head Ø 6 mm, 1 x starting head Ø 4.5 mm, 1 x coupling joint Ø 4.5 mm, 1 x adapter thread

ADVANTAGES

- Super thin pulling system
- RG4.5 - Guiding head with front thread RTG Ø 3 mm incl. swivel
- Automatic glide-back protection (only stops the RG4.5 guiding head)
- 14-pieces accessory box
- Total breaking load 100 kg
- Extremely shock-resistant box
- Suitable for occupied pipes or fiber optical cable laying (FTTH)

INFORMATION

Compatible with:

RC2 Inspection camera

30 m - Item no.: 10140

50 m - Item no.: 10141

**RC3 Inspection camera (digital)**

15 m - Item no. 10214

