

GF4.5 Profi-Set fiberglass rod Ø 4,5 mm

for pipe diameter 30 - 80 mm, incl. double run-out system

Item no.: **10052** | **10055** | **10057** | **10047** | **10050**

VIDEO

GF4.5

Click here Video

KG 220

Click here Productinformation

Ergonomic holding and carrying handle

Lateral parking brake

RG7 - Guiding head with front thread and eyelet incl. swivel

Double run-out system, quick outlet and automatic run-out brake

Extendable standing feet and storage compartment incl. accessories

Beginning: RG7 - Guiding head incl. swivel Ø 7 mm, thread RTG Ø 6 mm, screwed onto strand

Ending: Ending joint, stainless steel, thread RTG Ø 6 mm

Attention! Electrical conductive

Detailed image

extendable standing feet

Lateral parking brake and double run-out systems (Quick outlet and automatic run-out brake)

Quick run with rollers

Automatic run-out brake

Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
4,5 mm	30 - 80 mm	120 mm	55 mm	1300 kg	220 kg

DATA

Recommended trade price in EURO / excluding VAT

ITEM NO.	10052	10055	10057	10047	10050
PRICE €	€ 280,00	€ 307,00	€ 335,00	€ 361,00	€ 416,00
LENGTH	30 m	40 m	50 m	60 m	80 m
WEIGHT	4,84 kg	5,08 kg	5,32 kg	5,56 kg	6,04 kg
MATERIAL ROD	Fiberglass core with PP sheath				
BENDING RADIUS	120 mm				
PIPE Ø	optimal from 30 - 80 mm				
DIMENSION	H: 365 x B 260 x H 454 mm				
TOTAL BREAKING LOAD	220 kg				

DESCRIPTION

GF4.5 fiberglass rod (duct rodders) Ø 4.5 mm Profi-Set - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (CDP/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake, extendable feet and storage compartment for accessories. Fiberglass rod breaking load 1300 kg, total breaking load 220 kg.

Optimal field of application: for pipe diameters 30 mm - 80 mm.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x GF4.5 fiberglass rod Ø 4,5 mm Profi-Set, stainless steel ending joint on both sides (start/end), 1 x steel reel Ø 330 mm incl. double run-out system, extendable feet and storage compartment, additional accessories: 1 x RG7 RUNPOGLIDER with thread and swivel, 2 x ending joint, 1 x coupling joint, 1 x shackle, 1 x special glue, 1 x roller

ADVANTAGES

- incl. steel reel Ø 330 mm
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 1300 kg
- Total breaking load 220 kg
- Bending radius with ending joint 120 mm
- Bending radius only rod 55 mm

INFORMATION

Compatible with:

RC2 Inspection camera

30 m - Item no.: 10140

50 m - Item no.: 10141

RC3 Inspection camera (digital)

15 m - Item no. 10214

