

GF4.5 Standard-Set Fiberglass rod Ø 4,5 mm

for pipe diameter 30 - 80 mm, incl. double run-out system

Item no.: 10054 | 10056 | 10058 | 10048 | 10051



VIDEO

GF4.5

Click here Video

KG 220

Click here Productinformation

Ergonomic holding and carrying handle

Lateral parking brake

RG7 - Guiding head with front thread and eyelet incl. swivel

Double run-out system, quick outlet and automatic run-out brake

Beginning: RG7 - Guiding head with swivel Ø 7 mm, RTG Ø 6 mm thread, screwed to strand

Ending: Ending joint, stainless steel, thread RTG Ø 6 mm

Attention! Electric conductive

Quick run with rollers

Automatic run-out brake

Rod	rec. pipe diameter Ø	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
4,5 mm	30 - 80 mm	120 mm	55 mm	1300 kg	220 kg

DATA	Recommended trade price in EURO / excluding VAT				
ITEM NO.:	10054	10056	10058	10048	10051
PRICE €	€ 202,00	€ 228,00	€ 254,00	€ 279,00	€ 335,00
LENGTH	30 m	40 m	50 m	60 m	80 m
WEIGHT	4,00 kg	4,24 kg	4,50 kg	4,70 kg	5,20 kg
MATERIAL ROD	Fiberglass core with PP sheath				
BENDING RADIUS	120 mm				
PIPE Ø	optimal von 30 - 80 mm				
DIMENSION	L 365 x W 260 x H 435 mm				
TOTAL BREAKING LOAD	220 kg				

ADVANTAGES

- incl. steel reel Ø 330 mm
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 1300 kg
- Total breaking load 220 kg
- Bending radius with ending joint 120 mm

DESCRIPTION

Standard set fiberglass rod (duct rodders) Ø 4,5 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (CDP/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake. Fiberglass rod breaking load 1300 kg, total breaking load 220 kg. Optimal field of application: for pipe diameters 30 mm - 80 mm.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x Standard-Set fiberglass rod Ø 4,5 mm, stainless steel ending joint on both sides (start/end), 1 x steel reel Ø 330 mm incl. double run-out system, 1 x RUNPOGLIDER with thread and swivel

INFORMATION

Compatible with:

RC2 Inspection camera

30 m - Item no.: 10140
50 m - Item no.: 10141



Click here Productinformation

RC3 Inspection camera (digital)

15 m - Item no. 10214



Click here Productinformation