

GF6 Standard-Set Fiberglass rod Ø 6 mm

for pipe diameter 40 - 100 mm, incl. double run-out system

Item no.: **10060** | **10062** | **10063** | **10064** | **10066**

VIDEO

GF6

Click here Video

Ergonomic holding and carrying handle

Lateral parking brake

RG7 - Guiding head with front thread and eyelet incl. swivel

Double run-out system, quick outlet and automatic run-out brake

KG 320

Click here Productinformation

Attention! Electric conductive

Beginning: RG7 - Guiding head with swivel Ø 7 mm, RTG Ø 6 mm thread, screwed to strand

Ending: Ending joint, stainless steel, thread RTG Ø 6 mm

Quick run with rollers

Automatic run-out brake

Rod	rec. pipe diameter Ø	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
6 mm	40 - 100 mm	168 mm	80 mm	2200 kg	320 kg

DATA					Recommended trade price in EURO / excluding VAT				
ITEM NO.:	10060	10062	10064	10066					
PRICE €	€ 275,00	€ 303,00	€ 335,00	€ 400,00					
LENGTH	40 m	50 m	60 m	80 m					
WEIGHT	6,77 kg	7,19 kg	7,56 kg	8,36 kg					
MATERIAL ROD	Fiberglass core with PP sheath								
BENDING RADIUS	120 mm								
PIPE Ø	optimal for tube diameter 40 - 100 mm								
DIMENSION	H: 550 x B 270 x H 625 mm								
TOTAL BREAKING LOAD	320 kg								

DESCRIPTION

GF6 fiberglass rod (duct rodders) Ø 6 mm Standard-Set - RTG Ø 6 mm thread with robust steel reel Ø 530 mm (CDP/powder coated) with new double run-out system (automatic run-out brake and quick run-out), additional parking brake. Fiberglass rod breaking load 2200 kg, total breaking load 320 kg.

Optimal field of application: for pipe diameters 40 mm - 100 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x GF6 Fiberglass rod Ø 6 mm Standard-Set, stainless steel ending joint on both sides (start/ending), 1 x steel reel Ø 530 mm incl. double run-out system.

ADVANTAGES

- Incl. steel reel Ø 530 mm
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 2200 kg
- Total breaking load 320 kg
- Bending radius with ending joint 168 mm

INFORMATION

Compatible with:

RC2 Inspection camera

30 m - Item no.: 10140

50 m - Item no.: 10141

RC3 Inspection camera (digital)

15 m - Item no. 10214

