

**GF7.5** Fiberglass rod Ø 7,5 mm

for pipe diameter 50 - 120 mm, incl. double run-out-system

Item. no. **10076** | **10077** | **10078** | **10079** | **10080** | **10091**

**VIDEO**

GF7.5

Click here Video

**KG 400**  
Ø 7,5 mm

Click here Productinformation

- Ergonomic holding and carrying handle
- Autom. run-out brake
- Lateral parking brake
- Meter counter with hardened thumb wheel
- Quick run with mounted rollers
- Mobile reel CDP / powder-coated
- 2 x threaded bolts (for roller or starting head)

**Rod tip:** Shackle, stainless steel, RTG Ø 12 mm thread, screwed to strang

**Rod end:** Ending joint, stainless steel, RTG Ø 12 mm thread

**Double run-out-system**  
(Quick run and automatic run-out brake)

Quick run with mounted rollers

Automatic run-out brake rollers

Meter counter with hardened thumb wheel

Additional option: Adaptable leading heads

6-digit roller counter with meter and 10 cm steps

13-parts flexible leading head-set

| Rod    | Rec. pipe diameter | Bending radius w. e. joint | Bending radius rod | Breaking load | Total breaking load |
|--------|--------------------|----------------------------|--------------------|---------------|---------------------|
| Ø      |                    |                            |                    |               |                     |
| 7,5 mm | 50 - 120 mm        | 500 mm                     | 115 mm             | 3400 kg       | 400 kg              |

| DATA                | Recommended trade price in EURO / excluding VAT |          |          |          |          |          |
|---------------------|-------------------------------------------------|----------|----------|----------|----------|----------|
| ITEM. NO.           | 10076                                           | 10077    | 10078    | 10079    | 10080    | 10091    |
| PRICE €             | 455,00                                          | 477,00   | 497,00   | 539,00   | 576,00   | 610,00   |
| LENGTH              | 40 m                                            | 50 m     | 60 m     | 80 m     | 100 m    | 120 m    |
| WEIGHT              | 18,17 kg                                        | 18,71 kg | 19,33 kg | 20,70 kg | 21,00 kg | 22,00 kg |
| MATERIAL ROD        | Fiberglass core with PP sheath                  |          |          |          |          |          |
| BENDING RADIUS      | 500 mm                                          |          |          |          |          |          |
| PIPE Ø              | optimal from 50 - 120 mm                        |          |          |          |          |          |
| DIMENSION           | L 830 mm   W 400 mm   H 900 mm                  |          |          |          |          |          |
| TOTAL BREAKING LOAD | 400 kg                                          |          |          |          |          |          |

**DESCRIPTION**

GF7.5 glass fibre rod, Ø 7,5 mm – cable pulling tool with a robust, mobile steel reel (KTL-coated/powder-coated), Ø 730 mm, integrated metre counter and RUNPOTEC threaded RTG, Ø 12 mm. The integrated metre counter, featuring a mechanical counter mechanism, a hardened knurled wheel and a 6-digit roller counter, enables precise length measurement with metre and 10-cm displays. The new dual-feed system, with an automatic feed brake and quick-release feed, allows for controlled and efficient operation. The additional locking brake secures the reel and prevents accidental rotation. The shackle features an adapter thread to RTG Ø 6 mm, allowing various accessories such as RUNPOSTICKS, guide probes, cable pulling socks and the RC2 or RC3 inspection camera to be easily attached. The fiberglass rod has a breaking load of up to 3400 kg. The total breaking load, including the end sleeve, is 400 kg. The bending radius is 115 mm on the rod and 500 mm with the sleeve.

**Ideal application:** for pipe diameters from 50 mm to 120 mm.

**Scope of supply:** 1 x GF7.5 Fiberglass rod Ø 7,5 mm, stainless steel ending joint (start/end) 1 x steel reel Ø 730 mm mobile incl. double run-out-system, 1 x meter counter, 1 x shackle

**ADVANTAGES**

- Incl. steel reel and meter counter
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 3400 kg
- Total breaking load 400 kg
- Bending radius only rod 115 mm
- Bending radius with ending joint 500 mm

**INFORMATION**

Compatible with:

**RC2 Inspection camera**  
50 m - Item no.: 10141



**RC3 Inspection camera (digital)**  
15 m - Item no. 10214

