

GF7.5 Replacement fiberglass rod Ø 7,5 mm

Cable pulling system for pipe diameter 50–120 mm

Item no.: **20368** | **20369** | **20370** | **20371** | **20372** | **20414**

VIDEO

GF7.5 / GF9

Click here Video

KG
400

Ø 7,5 mm

Click here Productinformation

Repair instruction coupling joint

Repair instruction ending joint

Rod	Rec. pipe diameter	Bending radius	Bending radius rod	Breaking load	Total breaking load
Ø 7,5 mm					
7,5 mm	50 - 120 mm	500 mm	115 mm	3400 kg	400 kg

DATA

Recommended trade price in EURO / excluding VAT

ITEM NO.:	20368	20369	20370	20371	20372	20414
PRICE €	130,00	146,00	166,00	207,00	244,00	281,00
LENGTH	40 m	50 m	60 m	80 m	100 m	120 m
WEIGHT	2,60 kg	3,25 kg	3,90 kg	5,20 kg	6,50 kg	7,80 kg
MATERIAL ROD	Fiberglass core with PP sheath					
BENDING RADIUS	500 mm					
PIPE Ø	optimal from 50 - 120 mm					
DIMENSION	H 110 mm x DM 730 mm					
TOTAL BREAKING LOAD	400 kg					

DESCRIPTION

GF7.5 Replacement fiberglass rod, Ø 7.5 mm, with stainless steel end sleeves mounted on both ends and a RUNPOTEC RTG thread, Ø 12 mm. This high-quality fiberglass rod with a PP coating offers excellent shear stability and a rod breaking load of up to 3,400 kg. The total breaking load, including the end sleeves, is 400 kg. The bending radius is 115 mm for the rod itself and 500 mm with the end sleeves.

The replacement fiberglass rod was specifically developed as a replacement part for the RUNPOTEC GF7.5 cable pullers and comes pre-equipped with end sleeves on both ends. This allows it to be easily inserted into the existing steel reel and used immediately.

Damaged or broken glass fiber rods do not need to be completely replaced. Using the RUNPOTEC repair kit, the glass fiber rod can be repaired quickly and easily. Depending on the type of damage, either a connecting sleeve or an end sleeve is used, ensuring that the glass fiber rod can once again be used reliably.

Ideal area of application: for pipe diameters from 50 mm to 120 mm.

Scope of supply: 1 x GF7.5 Replacement fiberglass rod Ø 7,5 mm, ending joint on both sides (start/end)

ADVANTAGES

- Fiberglass rod breaking load 3400 kg
- Total breaking load 400 kg
- Bending radius with ending joint 500 mm
- Bending radius only rod 115 mm
- Pipe diameter 50 - 120 mm

INFORMATION

Suitable products:

GF7.5 Fiberglass rod Ø 7,5 mm

- 40 m - Item no.: 10076
- 50 m - Item no.: 10077
- 60 m - Item no.: 10078
- 80 m - Item no.: 10079
- 100 m - Item no.: 10080
- 120 m - Item no.: 10091



Click here Productinformation

GF7.5 Repairing Kit

Item no.: 20384



Click here Productinformation