

**GF9** Fiberglass rod Ø 9 mm

for pipe diameter 60 - 200 mm, incl. double run-out-system

Item. no. **10081** | **10082** | **10083** | **10084** | **10085** | **10086** | **10110**

**VIDEO**

GF9

Click here Video

**KG 460**

Ø 9 mm

- Ergonomic holding and carrying handle
- Autom. run-out brake
- Lateral parking brake
- Meter counter with hardened thumb wheel
- Quick run with mounted rollers
- Mobile reel CDP / powder-coated
- 2 x threaded bolts (for roller or starting head)

**Rod tip:** Shackle, stainless steel, RTG Ø 12 mm thread, screwed to strang

**Rod end:** Ending joint, stainless steel, RTG Ø 12 mm thread

Click here Product-information

**Double run-out-system**  
(Quick run and automatic run-out brake)

Quick run with mounted rollers

Automatic run-out brake rollers

Meter counter with hardened thumb wheel

Additional option: Adaptable leading heads

6-digit roller counter with meter and 10 cm steps

13-parts flexible leading head-set

| Rod  | Rec. pipe diameter | Bending radius w. e. joint | Bending radius rod | Breaking load | Total breaking load |
|------|--------------------|----------------------------|--------------------|---------------|---------------------|
| Ø    |                    |                            |                    |               |                     |
| 9 mm | 60 - 200 mm        | 620 mm                     | 140 mm             | 4500 kg       | 460 kg              |

| DATA                |                                |        |        |        |        |        |        | Recommended trade price in EURO / excluding VAT |  |  |  |  |  |  |  |
|---------------------|--------------------------------|--------|--------|--------|--------|--------|--------|-------------------------------------------------|--|--|--|--|--|--|--|
| ITEM. NO.           | 10081                          | 10082  | 10083  | 10084  | 10085  | 10086  | 10110  |                                                 |  |  |  |  |  |  |  |
| PRICE €             | 458,00                         | 489,00 | 519,00 | 576,00 | 624,00 | 656,00 | 747,00 |                                                 |  |  |  |  |  |  |  |
| LENGTH              | 40 m                           | 50 m   | 60 m   | 80 m   | 100 m  | 120 m  | 150 m  |                                                 |  |  |  |  |  |  |  |
| WEIGHT KG           | 19,37                          | 20,61  | 21,55  | 22,58  | 25,27  | 26,00  | 30,07  |                                                 |  |  |  |  |  |  |  |
| MATERIAL ROD        | Fiberglass core with PP sheath |        |        |        |        |        |        |                                                 |  |  |  |  |  |  |  |
| BENDING RADIUS      | 620 mm                         |        |        |        |        |        |        |                                                 |  |  |  |  |  |  |  |
| PIPE Ø              | optimal from 60 - 200 mm       |        |        |        |        |        |        |                                                 |  |  |  |  |  |  |  |
| DIMENSION           | L 830 mm   W 400 mm   H 900 mm |        |        |        |        |        |        |                                                 |  |  |  |  |  |  |  |
| TOTAL BREAKING LOAD | 460 kg                         |        |        |        |        |        |        |                                                 |  |  |  |  |  |  |  |

**DESCRIPTION**

GF9 Glass fibre rod Ø 9 mm – cable pulling tool with robust, mobile steel reel (KTL-coated/powder-coated) Ø 730 mm, integrated metre counter and RUNPOTEC threaded RTG Ø 12 mm. The integrated metre counter, featuring a mechanical counter mechanism, a hardened knurled wheel and a 6-digit roller counter, enables precise length measurement with metre and 10-cm displays. The new dual-feed system, with an automatic feed brake and quick-release feed, allows for controlled and efficient operation. The additional locking brake secures the reel and prevents accidental rotation. The shackle features an adapter thread to RTG Ø 6 mm, allowing various accessories such as RUNPOSTICKS, guide probes, cable pulling socks and the RC2 or RC3 inspection cameras to be easily attached. The fiberglass rod has a breaking load of up to 4500 kg. The total breaking load, including the end sleeve, is 460 kg. The bending radius is 140 mm for the rod and 620 mm with the sleeve.

**Ideal application:** for pipe diameters from 60 mm to 200 mm.

**Scope of supply:** 1 x GF9 Fiberglass rod Ø 9 mm, stainless steel ending joint (start/end) 1 x steel reel Ø 730 mm mobile incl. double run-out-system, 1 x meter counter, 1 x shackle

**ADVANTAGES**

- Incl. steel reel and meter counter
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 4500 kg
- Total breaking load 460 kg
- Bending radius only rod 140 mm
- Bending radius with ending joint 620 mm

**INFORMATION**

Compatible with:

**RC2 Inspection camera**  
50 m - Item no.: 10141



Click here  
Productinformation

**RC3 Inspection camera (digital)**  
15 m - Item no. 10214

Click here  
Productinformation

