

RG7 GUIDING HEAD with front thread RTG Ø 6 mm

incl. unscrewable eyelet and swivel

Item no.: **20460**

Application images:

RC2 Inspection camera +
RG7 Guiding head
[Click here
Productinformation](#)
DATEN

empf. VK-Preis / exkl. MwSt.

ITEM NO.	20460
PRICE €	€ 29,00
WEIGHT	0,013 kg
DIMENSION	L 114 mm x B 14 mm x DM 7 mm
MATERIAL	Stainless steel
THREAD	RTG Ø 6 mm with front thread
EAN-CODE	9120045474855

DESCRIPTION

The RG7 RUNPOGLEITER (guide tip) with a front thread (RTG Ø 6 mm) is ideally suited for the RC2 and RC3 inspection cameras developed in-house by RUNPOTEC. This allows the inspection cameras to be easily adapted to various fibreglass rods as well as to the RUNPOSTICKS. It can also be used as a guide tip for all RUNPOTEC products with an RTG Ø 6 mm thread. It impresses with its excellent bending and gliding properties, as well as a high breaking load of up to 270 kg. All RUNPOTEC cable pulling sleeves with an RTG Ø 6 mm thread can also be attached to it. The included eyelet allows for immediate cable pulling. The extra-large eyelet opening ensures a high cable capacity of up to 7 x 2.5 mm². Suitable for RUNPOSTICKS, GF4.5 and GF6 fibre optic rods, as well as RC2 and RC3 inspection cameras.

Scope of supply: 1 x RG7 RUNPOGLIDER (guiding head) with front thread RTG Ø 6 mm, 1 x unscrewable eyelet RTG Ø 6 mm thread

ADVANTAGES

- Ideally suited for RC2 or RC3 inspection camera
- Adaptable to various fibreglass rods, RUNPOSTICKS etc.
- Extremely good bending and sliding behaviour
- High tensile load

INFORMATION

Compatible with:

RUNPOSTICKS

Item no.: 10016 - 17-parts

Item no.: 10020 - 19-parts

Item no.: 10173 - 35-parts

[Click here
Productinformation](#)
Fibreglass rods

GF4.5 and GF6

Length 30 - 80 m

[Click here
Productinformation](#)
RC2 Inspection camera

50 m - Item no.: 10141

[Click here
Productinformation](#)
RC3 inspection camera (digital)

15 m - Item no. 10214

[Click here
Productinformation](#)