

RP5 RUNPOTEC Polyester Ø 5,5 mm – incl. digital meter counter

optimal for pipe inner diameter 9 - 32 mm

Item no.: 10202 | 10203



VIDEO

RP5

Click here Video

KG 270

PATENTED

Click here Productinformation

Integrated digital meter counter – m/ft

Beginning:
RG7 - Guiding head incl. swivel Ø 7 mm

Glide back protection

Active
(Only stops RG7 Guiding head)

Triple twisted special polyester fish tape Ø 5,5 mm

Ending:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Attention!
Electrical conductive

Very narrow bending radius

R = 15 mm

Virtually break-free even with tightest radii

R

50 % less friction resistance

Only punctual contact

Total breaking load 270 kg

Strand + Pressing + Guiding head + Eyelet

Rod	Rec. pipe-ID Ø	Bending radius	Total breaking load incl. RG7 - RUNPOGLIDER
Ø			
5,5 mm	9 – 32 mm	15 mm	270 kg

DATA

Recommended trade price in EURO / excluding VAT

ITEM NO.	10202	10203
PRICE €	€ 170,00	€ 189,00 PROMOTION
LENGTH	20 m	30 m
WEIGHT	1,34 kg	1,65 kg
EAN-CODE	9120045477573	9120045477580
DIMENSION BOX	L 380 X W 310 X H 50 mm	
TOTAL BREAKING LOAD	270 kg (on the whole strap)	
ROD Ø	Ø 5,5 mm	
MATERIAL	triple twisted special polyester fish tape	
BENDING RADIUS	15 mm	
PIPE INNER Ø	optimally from 9 mm - 32 mm	

DESCRIPTION

The RP5 - RUNPOTEC Polyester Ø 5,5 mm is a cable pulling tool with digital meter counter. The triple-twisted special plastic tape with a diameter of 5,5 mm has an even better shearing effect than the 3 mm fiberglass rod; the frictional resistance is only half the normal value due to spot contact. The patented RG7 guiding head with swivel Ø 5,5 mm (pressed at the beginning and end of the tape) allows overcoming tight radii (bending radius 15 mm). The RP5 Ø 5,5 mm is stored in a jobsite suitable box incl. glide back protection (only stops the RG7 Guiding head). The unit of measurement of the metre counter can be changed from metric (m) to imperial (ft). The total breaking load of 270 kg refers to the entire pulling system. The cable pulling system is virtually breakage-free. The RP5 replacement strap cannot be stored in the box.

Optimal field of application: for pipe inner diameter Ø 9 mm - 32 mm.

Scope of supply: 1 x RP5 RUNPOTEC Polyester Ø 5,5 mm with digital meter counter in a plastic box, including 2 x RG7 RUNPOGLEITER with swivel (pressed on both sides)

ADVANTAGES

- Integrated digital meter counter
- Total breaking load 270 kg
- 2 x RG7 - Guiding head with swivel Ø 7 mm
- Glide back protection (only stops the RG7 Guiding head)
- Triple twisted special plastic tape Ø 5,5 mm
- 50 % less frictional resistance
- Virtually break-free, even with the tightest radii

INFORMATION**Compatible accessories:****RP5 Replacement fish tape**

20 m – Item no.: 20240

30 m – Item no.: 20241

**Cable pulling loop with hook**

(Quick release fastener) – set of 4

Item no.: 10159

