

RP5 Replacement fish tape Ø 5,5 mm

Cable pulling tool for pipe inner diameter Ø 9 - 32 mm

Item no.: 20240 | 20241 | 20242



VIDEO

RP5

Click here Video

KG 270

PATENTED

Click here Productinformation

Triple twisted special polyester fish tape Ø 5,5 mm

Beginning:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Ending:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Attention!
Electrical conductive

Very narrow bending radius

R = 15 mm

Virtually break-free, even with tightest radii

R

Total breaking load 270 kg

Strand + Pressing + Guiding head + Eyelet

KG 270

DATA	Recommended trade price in EURO / excluding VAT		
ITEM NO.	20240	20241	20242
PRICE €	€ 110,00	€ 126,00	€ 144,00
LENGTH	20 m	30 m	40 m
WEIGHT	0,46 kg	0,66 kg	0,86 kg
DIMENSION mm	35x500x500	45x500x500	55x500x500
EAN-Code	9120045472820	9120045472837	9120045472844
MATERIAL ROD	triple twisted special fish tape		
ROD Ø	5,5 mm		
BENDING RADIUS	15 mm		
TOTAL BREAKING LOAD	270 kg (on the whole strap)		
PIPE INNER Ø	optimal from 9 mm - 32 mm		

DESCRIPTION

The RP5 Replacement fish tape is a triple-twisted special plastic tape with a diameter of 5.5 mm has an even better shearing effect than the 3 mm fiber-glass rod; the frictional resistance is only half the normal value due to spot contact. The patented RG7 Guiding head with swivel Ø 5.5 mm (pressed at the beginning and end of the tape) allows overcoming tight radii (bending radius 15 mm). The incredible total breaking load of 270 kg refers to the entire pulling system. Labour- and time-consuming repair work is no longer necessary, as this cable pulling system is virtually breakage-free. The RP5 can be stored in a very practical box in lengths of 20 m and 30 m. The RP5 replacement strap 40 m cannot be stored in the box.

Optimal field of application: for pipe inner diameter 9 - 32 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x RP5 Replacement fish tape Ø 5,5 mm without box, including 2 x RG7 RUNPOGLIDER with swivel (pressed on both sides)

ADVANTAGES

- 50 % less friction resistance
- Total breaking load 270 kg
- 2 x RG7 - Guiding head with swivel Ø 7 mm
- Triple twisted special plastic tape Ø 5,5 mm
- 50 % less frictional resistance
- Virtually break-free, even with the tightest radii

INFORMATION**Compatible accessories**

RP5 - empty Box
Item no.: 30146



Click here
Productinformation

Cable pulling grip with quick release fastener

Ø 4 - 6 mm – Item no.: 20272

Ø 6 - 9 mm – Item no.: 20273

Ø 9 - 15 mm – Item no.: 20274

Click here
Productinformation

