

RP5 + XB 300 - Multi-Set

Cable roller system - stowed in RUNPOTEC system case

Item no.: 10171



VIDEO



XB 300

Click here Video

Click here
Product information


Description: XB 300 see Page 2

Description: RP5 see Page 3

Detailed image:



Advantages RP5:

Very narrow
bending radiusDetailed info
see page 3

Application images:

XB 300 with cable + drum



DATA	Recommended trade price in EURO / excluding VAT
ITEM NO.:	10171
PRICE €	€ 314,00
DIMENSION	L 437 mm x W 405 mm x H 137 mm
WEIGHT	5,19 kg
DIMENSION Ø	XB 300 - 300 mm Multifunction mandrel: Ø 430 mm
LOAD CAPACITY XB 300	300 kg
TOTAL BREAKING LOAD RP5	270 kg
EAN-CODE	9120045476552

DESCRIPTION

The multifunction mandrel has been specially developed for XB 300, XB 500 and XB 500 T cable rolling systems. Loose cable bundles can also be rolled by attaching them to the stainless-steel center mandrel and then folding out the 4 side brackets. The telescopic center mandrel measures 72 mm in diameter. It is therefore also ideal for rolling a thinner cable bundle with a small inner diameter or individual wires. The normal height of the multifunction mandrel is 196 mm, which can be extended up to max. 294 mm via the telescopic mechanism. This means high cable bundles or corresponding tube bundles can also be rolled. When the 4 side brackets are unfolded, there is a total contact surface of 430 mm in diameter. Ideally, this should correspond to the respective cable or tube bundle. A designated opening allows the unit to be combined with the RUNPOSTICKS.

Optimum area of application: : **XB300**: Rolling of (damaged) drums up to 300 kg as well as loose cable bundles or individual wires up to a max. height of 294 mm and a max. diameter of 430 mm, **RP5**: for pipe dimension 16 mm – 40 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x XB 300, 1 x Multifunction mandrel, 1 x RP5 – 30 m, 1 x RUNPOTEC system case

ADVANTAGES

- XB 300 Cable Roller
- Universal cable drum rewinder and unwinder
- Compact - lightweight
- Loadable up to 300 kg
- Excellent for damaged cable drums
- No cable clutter
- Non-slip and stable base

Multifunction mandrel

- Can be used in combination with XB 300, XB 500 and XB 500 T
- Allows loose cable bundles and individual wires to be rolled
- Telescopic centre mandrel, extendable up to 294 mm this allows high cable bundles or corresponding tube bundles to be accommodated

RP5 Cable pulling system

- 50 % less friction resistance
- 270 kg total breaking load
- Almost breakproof
- 2 x RG7 - guiding head with swivel Ø 7 mm
- Glide back protection (only stops the RG7 guiding head)

XB 300 Cable Roller

Loadable up to 300 kg

Item no.: **10137**

VIDEO



XB 300

Click here Video



XB Mandrel
Ø 45 mm
removable for
small drums

Click here
Productinformation

Possible applications



With clip system for the RM35 digital cable length measuring device

**DATA**

Recommended trade price in EURO / excluding VAT

ITEM NO.:	10137
PRICE €	€ 114,40
DIMENSION	H 100 x Ø 290 mm
DIAMETER Ø	300 mm
LOAD BEARING CAPACITY	300 kg
DRUM WIDTH	variable
WEIGHT	1,26 kg
HEIGHT	105 mm
MANDREL Ø MM	15 mm / 45 mm
EAN-CODE	9120045475623

DESCRIPTION

The compact XB 300 Cable roller is a universal cable winder/unwinder for all small to medium cable reels. The XB 300 Cable roller impresses with its small, light and flat design, but can still be loaded up to 300 kg.

Especially suitable for damaged cable drums.

It enables trouble-free and rational working without tangled cables. 6 rubberized feet ensure a non-slip and stable base. Optimal for protecting surfaces for already finished floor coverings. Due to the removable mandrel, cable drums with different hole sizes can be used.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x XB 300 Cable roller incl. XB mandrel

ADVANTAGES

- Universal cable drum rewinder and unwinder
- For all types of cables and cable drums even with very small inner diameters
- Compact - lightweight - 1.26 kg net weight
- Loadable up to 300 kg
- Excellent for damaged cable drums
- No cable clutter
- Trouble-free and rational work approach
- Non-slip and stable base

INFORMATION

Available as spare part

Multifunction mandrel

Item no.: 20696



Click here
Produktinformation

Alternative cable roller

XB 500 Cable Roller

Item no.: 10136



Click here
Produktinformation

RUNPOSTICKS ROT

Item no.: 20881



Click here
Produktinformation

RP5 RUNPOTEC Polyester Ø 5,5 mm – without meter counter

optimal for pipe diameter 16–40 mm

Item no.: 10013 | 10014



VIDEO

RP5

Click here Video

KG 270

PATENTED

Click here Productinformation

Beginning:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Glide back protection
Aktive (Only stops RG7 Guiding head)

Triple twisted special polyester fish tape Ø 5,5 mm

Ending:
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Attention!
electric conductive

Very narrow bending radius

R = 15 mm

Virtually break-free even with tightest radii

R

50 % less friction resistance

Only punctual contact

Total breaking load 270 kg

Strand + Pressing + Guiding head + Eyelet

KG 270

Rod	Rec. pipe-ID Ø	Bending radius	Total breaking load incl. RG7 - RUNPOGLIDER
Ø			
5,5 mm	9 – 32 mm	15 mm	270 kg

DATA

Recommended trade price in EURO / excluding VAT

ITEM NO.	10013	10014
PRICE €	€ 140,00	€ 162,00
LENGTH	20 m	30 m
WEIGHT	1,31 kg	1,62 kg
EAN-CODE	9120045472806	9120045472813
DIMENSION BOX	L 380 X W 310 X H 50 mm	
TOTAL BREAKING LOAD	270 kg (on the whole strap)	
ROD Ø	Ø 5,5 mm	
MATERIAL	triple twisted special polyester fish tape	
BENDING RADIUS	15 m	
PIPE INNER Ø	optimally from 9 mm - 32 mm	

DESCRIPTION

The RP5 - RUNPOTEC Polyester Ø 5.5 mm is a cable pulling tool without a meter counter. The triple-twisted special plastic tape with a diameter of 5.5 mm has an even better shearing effect than the 3 mm fiberglass rod; the frictional resistance is only half the normal value due to spot contact. The patented RG7 guiding head with swivel Ø 5.5 mm (pressed at the beginning and end of the tape) allows overcoming tight radii (bending radius 15 mm). The RP5 - RUNPOTEC Polyester Ø 5.5 mm is stored in a jobsite suitable and robust storage box with an ergonomic carrying handle. It is equipped with the new glide back protection (only stops the RG7 guiding head), which prevents the cable pulling strap from slipping back accidentally. The incredible total breaking load of 270 kg refers to the entire pulling system. Labour- and time-consuming repair work is no longer necessary, as this cable pulling system is virtually breakage-free.

Optimal field of application: for pipe inner diameter 9 - 32 mm

Scope of supply: 1 x RP5 cable pulling tape Ø 5,5 mm without meter counter in a plastic box, length: 20 m, including 2 x RG7 RUNPOGLIDER with swivel (pressed on both sides)

ADVANTAGES

- Total breaking load 270 kg
- 2 x RG7 - Guiding head with swivel Ø 7 mm
- Glide back protection (only stops the RG7 Guiding head)
- Triple twisted special plastic tape Ø 5,5 mm
- 50 % less frictional resistance
- Virtually break-free, even with the tightest radii

INFORMATION**Compatible accessories:****RP5 Replacement fish tape**

20 m – Item no.: 20240

30 m – Item no.: 20241

**Cable pulling loop with hook**

(Quick release fastener) – set of 4

Item no.: 10159

