

GF3 SLIM RG4.5 - Guiding head with front thread

for fiberglass rod Ø 3 mm, thread RTG Ø 3 mm

Item no.: 20956



VIDEO

GF3 SLIM

Click here Video

Only Ø 4,5 mm

Click here Productinformation

Storable in the GF3 SLIM accessory box

*Musterbild - Box nicht enthalten

Application - FTTH fiberglass installation

Speedpipe from Ø 5 mm
Innendiameter

Ideally suited for occupied pipes

RG4.5 - Guiding head Ø 4,5 mm

DATA	Recommended trade price in EURO / excluding VAT
ITEM NO.:	20956
PRICE €	€ 22,00
WEIGHT	0,0037 kg
DIMENSION GUIDING HEAD + EYELET	L 68 x W 13,50 x H 4,50 mm
BREAKING LOAD	100 kg
MATERIAL	Stainless steel
EAN-CODE	9120045477740

DESCRIPTION

The patented RG4.5 - Guiding head with front thread (RTG Ø 3 mm) including swivel is ideal for the GF3 SLIM fiberglass rod Ø 3 mm. With a maximum diameter of only Ø 4.5 mm, the guiding head is well-suited for retrofitting occupied pipes or laying fiber optic cables (FTTH - Fiber to the Home). Breaking load: 100 kg

Application film: you can watch a short, very informative application film by scanning the QR code or on www.runpotec.com.

Scope of supply: 1 x RG4.5 Guiding head with front thread RTG Ø 3 mm including swivel, 1 x pulling eyelet Ø 4.5 mm, 1 x starting head Ø 4.5 mm

ADVANTAGES

- Patented RG4.5 - Guiding head RTG Ø 3 mm
- Incl. swivel
- Ideal for retrofitting occupied pipes or laying glass fibre cables
- Breaking load 100 kg
- Stainless steel

INFORMATION

Use with:

GF3 SLIM - Cable pulling tool incl. digital meter counter
 20 m - Item no.: 10207
 30 m - Item no.: 10208
 50 m - Item no.: 10209



GF3 SLIM - Cable pulling tool without meter counter
 20 m - Item no.: 10210
 30 m - Item no.: 10211
 50 m - Item no.: 10212



GF3 SLIM Replacement fiberglass Ø 3 mm
 20 m - Item no.: 20952
 30 m - Item no.: 20953
 50 m - Item no.: 20954

