


SHACKLE with thread RTG Ø 12 mm

for Fiberglass rods GF7.5 - GF15

Item no.: **20383**

GF7.5/GF9

Click here Video

Cross
sectionRTG
Ø 12 mmRTG
Ø 6 mminkl. connection thread
(for flexible leading head
or small-sized cable
pulling grip incl. blind cap
(for thread protection))Click here
Productinformation

Application images:

**DATA**

Recommended trade price in EURO / excluding VAT.

ITEM NO.	20383
PRICE €	€ 27,80
WEIGHT	0,19 kg
DIMENSION	L 82 mm x B 42 mm x H 25 mm
THREAD	RTG Ø 12 mm incl. Connection thread RTG Ø 6 mm
MATERIAL	Stainless steel / Galvanized steel
EAN-CODE	9120045474305

DESCRIPTION

The robust shackle is ideal for attaching cables, pull-in wires or pull ropes and provides a reliable connection for various applications. It is compatible with GF7.5 – GF15 fiberglass rods. In addition, the shackle has a transition thread on RTG Ø 6 mm, which allows easy adaptation of guide rods (RUNPOSTICKS), guide probes, and cable pulling socks. Thanks to its high-quality workmanship made of stainless steel and galvanized steel, it impresses with its durability and high load capacity.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.RUNPOTEC.com.

Scope of supply: 1 x Shackle with RTG Ø 12, mm thread, 1 connection thread RTG Ø 6 mm

ADVANTAGES

- For attaching cables, pull wires or pull ropes
- RUNPOTEC RTG Ø 12 mm
- Incl. connection thread to adapt guide probes or small cable pulling grips
- Stainless steel / Galvanized steel

INFORMATION

Compatible with:

Fiberglass rods:

**GF7.5, GF9,
GF11, GF15**Click here
Productinformation